

# **CE440 SEAL COAT**

## **EPOXY SEALER**

## **ITEM NUMBER** CE440

## **DESCRIPTION**

CE440 Seal Coat is a low viscosity, two-component, solvent-free, moisture tolerant, high gloss multipurpose epoxy coating with high chemical resistant properties.

#### **INDUSTRY USES**

CE440 Seal Coat is designed for sealing interior and exterior slabs, epoxy grout and steel from water chloride and chemical attack. Was also designed and can be used for sealing in aggregate for skid-resistant overlays and sealing concrete for interior high gloss floors.

## **COVERAGE**

100 to 300 sq ft. per gallon depending on the porosity of the surface substrate.

#### **PACKAGING**

1 gal / 3.78 L units 3 gal / 11.36 L units 15 gal / 56.78 L units

#### **TECHNICAL DATA**

LABORATORY TESTS	RESULTS
Mix Ratio	2:1 by volume
D2393 Brookfield Visc - RV3 @ 20 rpm	1,500 cps
D2471 Gel Time @ 73° ± 2°F (23°C)	30 minutes
Tack Free Time	4 - 6 hours
Foot Traffic at 75°F	24 hours
Vehicle Traffic at 75°F	48 hours
Recoat time at 75°F	Within 24 hours

Shelf Life: 2 years in original unopened container. Storage Conditions: Store at 40°F – 95°F (5°C – 35°C). Condition material to: 65°F – 85°F (18°C – 29°C) before using.

VOC content: 0 g/L.

#### **LIMITATIONS**

Minimum application temperature is 40°F (5°C). Do not thin. Solvents will prevent proper care.

#### APPLICATION

Clean surface to remove all contaminants. Remove dust and debris by blowing off with oil-free compressed air. Mechanically mix component A with component B in a 2:1 by volume mix with Jiffy type mixer at low-speed (300 rpm) for a minimum of 3 minutes. Mix only the quantity that can be used within its gel time. Apply neat application of Seal Coat by squeegee at the specified rate.

Allow full cure before opening to traffic.

#### **CLEANUP**

Dispose of in accordance with current applicable local, state and federal regulations. Uncured material can be removed with Natural Clean or approved solvent. Cured material can only be removed mechanically.



## **CE440 SEAL COAT**

#### **LIMITED WARRANTY**

All information provided by Cornerstone Construction Material LLC (CCM) concerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with CCM's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of CCM's control are such that CCM assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the CCM product(s) must test the product(s) for suitability for the intended application and purpose before proceeding the full application of the product(s). CCM reserves the right to change the properties of its products without notice. All sales of CCM product(s) are subject to its current terms and conditions of sale.

Prior to each use of any CCM product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Safety Data Sheet which are available at www.ccmaterial.com. Nothing contained in any CCM materials relieves the user of the obligation to read and follow the warnings and instruction for each CCM product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use.

CCM warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet when used in accordance with the written instructions. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CCM SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. CCM SHALL NOT BE REPSONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.