



## CE550 SBA

### SEGMENTAL BRIDGE ADHESIVE

#### ITEM NUMBER CE550

**CE550** Segmental Bridge Adhesive (SBA) is a solvent free, two-component, high modulus, moisture-insensitive epoxy adhesive designed to bond and seal segmental precast elements. It conforms to the current ASTM C 881, Type VI and VII requirements. It is available in three application temperature ranges, LT (low temperature), MT (medium temperature), and HT (high temperature). Each is specifically designed for use in the following temperature ranges:

SBA-LT: 40°F - 65°F (4°C - 18°C)  
SBA-MT: 60°F - 85°F (16°C - 29°C)  
SBA-HT: 80°F - 115°F (27°C - 46°C)

#### ➤ USE

A high-performance adhesive for bonding and sealing segmental precast elements with internal tendons and for span-by-span erection when temporary post tensioning is applied. It can also be used as a repair mortar for concrete patching and structure repair.

#### ➤ BENEFITS

Insensitive to moisture during application, curing, and in service.  
Three formulations accommodate wide temperature range installations.  
High strength, high modulus.  
Non-sag consistency allows vertical and overhead installation.  
Lubricates surfaces for easy location & positioning of shear keys.

#### ➤ COVERAGE

At a film thickness of 1/16" (1.6 mm) the yield is 26 sq. ft. / gal. (2.4 sq. m. / L).  
Coverage rate is approximate and depends on porosity and profile of concrete.

#### ➤ PACKAGING

Factory proportioned 3 gallon unit.  
Shelf Life is two years in original unopened container.  
Store dry at 40°F - 95°F (4°C - 35°C). Condition material to 70°F - 75°F (21°C - 24°C) before using.

#### ➤ TECHNICAL DATA

| Laboratory Test                       | Results                | Specification      |
|---------------------------------------|------------------------|--------------------|
| ASTM C881 Consistency                 | ¼ inch (6.0 mm) no sag | ¼ inch no sag      |
| ASTM C881 Gel Time                    | 45 minutes             | 30 minutes minimum |
| Open Time (65°F, 85°F, 115°F)         | 60 minutes             |                    |
| ASTM C882 Contact Strength, 2-day     | 1,400 psi (9.7 MPa)    | 1,000 psi minimum  |
| ASTM D695 Compressive Strength 1-day  | 3,000 psi (20.7 MPa)   | 2,000 psi minimum  |
| ASTM D695 Compressive Strength 2-day  | 7,000 psi (48.3 MPa)   | 6,000 psi minimum  |
| ASTM C882 Bond Strength 2-day Moist   | 1,400 psi (9.7 MPa)    | 1,000 psi minimum  |
| ASTM D648 Heat Deflection Temperature | 140 °F (60 °C)         | 120 °F             |

#### ➤ APPLICATION

**Surface Preparation:** Surfaces must be clean, sound, and free from frost, standing water, laitance, form release agents, curing compounds and other contaminants. Surfaces may be dry or damp.

**Mixing:** SBA is supplied in factory proportioned units comprised of the correct quantities of Part A (resin) and Part B (hardener). Pre-mix each component separately using a slow speed drill (400 rpm).

Pour Part B to Part A pail and mix thoroughly for 3 minutes until a uniform gray color is achieved. Mix only the quantity that can be used within its gel time.

**Application:** Using a trowel, brush, or gloved hand, apply SBA to the prepared surfaces of both segments to be joined. Work into the substrate to ensure complete wetting out of the surface area. Secure the segments firmly together within the open working time of the epoxy.

#### ➤ CAUTIONS

Component A – Irritant



## CE550 SBA

### SEGMENTAL BRIDGE ADHESIVE

Component B – Corrosive

Product is a strong sensitizer. Use of safety goggles and chemical resistant gloves are recommended.

Use of a NIOSH/MSHA organic vapor respirator is recommended if ventilation is inadequate.

Avoid breathing vapors.

Avoid skin contact.

#### ➤ **FIRST AID**

Cured SBA is innocuous.

For uncured SBA:

SKIN CONTACT – Remove contaminated clothing. Remove product with an absorbent cloth. Wash skin area thoroughly with soap and water. (Solvents should not be used because they carry product into the skin.)

EYE CONTACT – Flush eyes immediately with water for a minimum of 15 minutes. Contact physician immediately.

RESPIRATORY PROBLEMS – Seek fresh air and/or medical attention.

#### ➤ **CLEANUP**

Uncured SBA can be removed with approved solvent. Collect with absorbent material. Flush area with water. Dispose of in accordance with local, state, and federal disposal regulations. Cured SBA can only be removed mechanically.

### **LIMITED WARRANTY**

All information provided by Cornerstone Construction Material LLC (CCM) concerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with CCM's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of CCM's control are such that CCM assumes no liability for the provision of such information, advice, recommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the CCM product(s) must test the product(s) for suitability for the intended application and purpose before proceeding the full application of the product(s). CCM reserves the right to change the properties of its products without notice. All sales of CCM product(s) are subject to its current terms and conditions of sale.

Prior to each use of any CCM product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Safety Data Sheet which are available at [www.ccmaterial.com](http://www.ccmaterial.com). Nothing contained in any CCM materials relieves the user of the obligation to read and follow the warnings and instruction for each CCM product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use.

CCM warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet when used in accordance with the written instructions. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CCM SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. CCM SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**