



# ROAD Rx

## SOIL STABILIZER AND DUST SUPPRESSANT

### DESCRIPTION

FasTrac ROAD Rx is an effective, economical, and environmentally friendly soil stabilizer and dust suppressant. Unique hybrid chemistry chemically reacts with lime in the soil to effectively create a binder/dust suppressant. FasTrac ROAD Rx increases the service life of gravel roads and significantly reduces maintenance costs.

### FEATURES

- Environmentally friendly – safe to use
- Concentrated – economical
- Proven Technology - effective
- Can be used to augment cement & lime soil stabilization

### PACKAGING

- 55 gal / 208 L drums
- 275 gal / 1041 L totes

### APPLICATION RATES

Dilute FasTrac ROAD Rx 100:1 with water. Application rate for FasTrac ROAD Rx Ready-to-Use solution: 0.5 gallons per square yard per inch stabilized.

- 1 gallon per sq/yd stabilizing 2"
- 2 gallons per sq/yd stabilizing 4"
- 3 gallons per sq/yd stabilizing 6"
- 4 gallons per sq/yd stabilizing 8"
- 5 gallons per sq/yd stabilizing 10"
- 6 gallons per sq/yd stabilizing 12"

### LIMITATIONS

Do not allow product to freeze  
Shelf Life: 2 years in original unopened container  
Storage Conditions: 40°F-95°F (5°C-5°C)

### CLEAN UP

Collect with absorbent material. Flush area with water. Dispose of in accordance with local, state and federal disposal regulations.

### LIMITED WARRANTY

All information provided by Cornerstone Construction Material LLC (CCM) concerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled and applied under normal conditions in accordance with CCM's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of CCM's control are such that CCM assumes no liability for the provision of such information, advice, rec-

ommendations or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations or instructions related to its products. The user of the CCM product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). CCM reserves the right to change the properties of its products without notice. All sales of CCM product(s) are subject to its current terms and conditions of sale.

Prior to each use of any CCM product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Safety Data Sheet which are available at [www.ccmaterial.com](http://www.ccmaterial.com). Nothing contained in any CCM materials relieves the user of the obligation to read and follow the warnings and instructions for each CCM product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use.

CCM warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet when used in accordance with the written instructions. User determines suitability of product for intended use and assumes all risks. Buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor.

**NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CCM SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. CCM SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

### MANUFACTURER

Cornerstone Construction Material, LLC  
1150 SE Hamblen Rd.  
Lee's Summit, MO 64081  
816-380-1082  
[www.ccmaterial.com](http://www.ccmaterial.com)