

FasTrac Retarder

SET TIME RETARDER FOR FASTRAC CEMENTITIOUS PRODUCTS



Technical Data Sheet

PRODUCT DESCRIPTION


FasTrac Retarder is a water- based set retarder for use with FasTrac Concretes and Cementitious Products. FasTrac Retarder will compensate for hot weather conditions and delays between mixing and placement. FasTrac Retarder can aid in prevention of cold joints, loss of workability and finishing in hot weather conditions.

APPLICATIONS

- Hot Weather Concreting
- Long-Distance Placements
- **Traffic Pavement Rehabilitation**
- Mass or Large Volume Placements

USE AND DOSAGE

FasTrac Retarder should be used when slower setting of FasTrac Concretes and Cementitious Products is desired. Typical dosage rates may be as follows:



•The dose of retarder is approximate. It may vary for different mix designs.

FEATURES

- **Dosage Specific**
- Easy to Use
- Non-Hazardous
- Wide Temperature Range

DISPERSION AND MIXING

FasTrac Retarder is a liquid and should be completely dispersed into mix water before adding FasTrac Concretes or Cementitious Products. Stir or mix accelerator in pail for 60 seconds to eliminate any effects of settling. Add recommended amount of mix water to mixer and add specified dosage of FasTrac Retarder to water. Mix until Retarder is fully dispersed in water than add FasTrac Concrete or Cementitious Product. Do not add accelerator after FasTrac Cementitious Products is added to the mixer. As a water-based product, ensure Retarder dosage is considered for total product mix water.

SHELF LIFE AND STORAGE

6 months from date of manufacture in original unopened containers when stored under dry, weather-proof conditions.

Revised: 11-15-2023 SR

Store product at temperatures between 40°F and 90°F (4.4°C and 32°C).

PACKAGING

50 lb. pails.

HEALTH AND SAFETY INFORMATION

EP OUT OF THE REACH OF CHILDREN, Prevent contact with skin and eyes. Prevent inhalation of dust. Do NOT take internally, Use only with adequate ventilation. Use impervious gloves, eye protection and if the TLV is exceeded or is used in a poorly ventilated area, use NIOSH/MSHA approved respiratory protection in accordance with applicable federal, state, and local regulations. ase of eye contact, flush thoroughly with water for at least 15 minutes, and seek medical attention. In case of skin contact, wash affected areas with soap and water. If the irritation persists seek medical attention. Remove and wash contaminated clothing. If inhalation causes physical discomfort, remove to fresh air. If the discomfort persists, breathing difficulty occurs, or if

LIMITED WARRANTY

oncerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled, and applied under normal rates, storage and handling conditions, actual site conditions and other factors outside of CCM's current are such that CCM assumes no liability for the provision of such information, advice, recommendations, or instructions related to its products. In such as a consistent of the product, for such table in the product, for the provision of such information, advice, recommendations, or instructions related to its products. The use of the CCM product(j) four steaders the reported; of large products without notice. All sales of CCM product, for the such products without notice. All sales of CCM products are always read and follow the warmings and instructions on the product's most current Technical Data Sheet, product label and Salety Data Sheet price to repoduct use. Commandation of the control and product use. Commandation of the control and product use of the control and product use of the control and product use. Commandation of the control and product use of the control and product use. Commandation of the control and product use of the control and product use. Commandation of the control and product use of the control and product use. Commandation of the control and product use of the control and product use. Commandation of the control and product use of the control and product use. Commandation of the control product use of the control and product use. Commandation of the contr

ery reasonable effort is made to apply exacting standards both in the manufacture of "FasTrac Retarder" product and in the information which we are unable effort is made to apply exacting standards both in the manufacture of "FasTrac Retarder" product and in the information which we are unable effort is made to apply exacting standards both in the manufacture of "FasTrac Retarder" product and in the information which we warrant our products to be good quality and will replace or, a our election, refund the purchase price of any architecture. Statisfactory results depend on one of the individual products and or investigation are unable to the purchase price of any architecture of the individual products and or investigation are unable to the purchase price of any architecture of the individual products and or investigation are unable to the purchase price of any architecture of the purchase price of any architecture of the individual products and in the purchase price of any architecture of any architecture of the purchase price of any architecture of any a





www.fastracproducts.com



816-380-4747



sales@fastracproducts.com



🤶 Lee's Summit, MO 64081