



# FasTrac Cure & Seal 1315

SOLVENT BASED CURING AND SEALING COMPOUND



## Technical Data Sheet

### PRODUCT DESCRIPTION

FasTrac Cure & Seal 1315 is a clear, VOC compliant, solvent based, non-yellowing, acrylic copolymer curing and sealing compound containing 25 % solids. Cure & Seal 1315 provides the water retention qualities essential to proper curing with the added feature of a clear membrane that effectively seals, dustproofs, and beautifies new or old concrete. FasTrac Cure & Seal 1315 meets the requirements of ASTM C 309 and ASTM C 1315.

### WHERE TO USE

FasTrac Cure & Seal 1315 is designed for use as a curing and sealing compound for freshly placed concrete. A color stable, high gloss, pure acrylic system also protects new construction against spills, stains, producing an easy to clean substrate for final walkthroughs. Use to protect and seal stamped decorative concrete, stucco, brick, and exposed aggregate concrete.

### APPLICATIONS

- Decorative Concrete
- Stucco
- Brick
- Exposed Aggregate Concrete

### FEATURES

- Excellent moisture retention properties
- U.V. stable, non-yellowing
- Seals and hardens surfaces
- Rapid drying for fast turnaround

### USE

- **New Concrete:** Apply FasTrac Cure & Seal 1315 immediately after concrete surface water has disappeared and the freshly placed concrete can support weight of the finisher. Apply uniformly with sprayer, roller, or brush. Additional sealing coats may be applied at later times. Do not alter product by thinning or reducing. Apply uniformly without puddles.
- **Existing Concrete:** All surfaces should be clean and dry. Remove all compounds, grease, dirt, and other bond inhibiting contaminants. Apply by sprayer, brush, or roller uniformly over surfaces.

### COVERAGE

Approximately 200 to 400 square feet (18.6 to 37.2 meters) per gallon depending upon concrete properties and age.

TYPICAL PROPERTIES at 75° F (23.8° C)	
TEST METHOD	RESULTS
Percentage Solids	25%
Color	Clear
ASTM C 156 Moisture Retention	< 0.11 lbs. per square feet (0.55 kg per square meter)
Dry Time	1-2 hours

### HEALTH AND SAFETY INFORMATION

Warning: Flammable liquid. Keep away from sparks and open flame. Use proper PPE (eye and skin protection) when using. Read SDS before use. PROP 65: This product contains chemicals known by the state of CA to cause cancer.

### LIMITED WARRANTY

LIMITED WARRANTY All information provided by Cornerstone Construction Material LLC (CCM) concerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled, and applied under normal conditions in accordance with CCM's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of CCM's control are such that CCM assumes no liability for the provision of such information, advice, recommendations, or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations, or instructions related to its products. The user of the CCM product(s) must test the product(s) for suitability for the intended application and purpose before proceeding the full application of the product(s). CCM reserves the right to change the properties of its products without notice. All sales of CCM product(s) are subject to its current terms and conditions of sale. Prior to each use of any CCM product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Safety Data Sheet which are available at [www.ccmaterial.com](http://www.ccmaterial.com). Nothing contained in any CCM materials relieves the user of the obligation to read and follow the warnings and instructions for each CCM product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. CCM warrants this product for one year from the date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet when used in accordance with the written instructions. User determines suitability of product for intended use and assumes all risks. The buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CCM SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. CCM SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Every reasonable effort is made to apply exacting standards both in the manufacture of "FasTrac Cure & Seal" product and in the information which we issue concerning these products and their use. We warrant our products to be good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only on quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, Cornerstone Construction Material LLC (CCM) makes no warranty or guarantee, express or implied, including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Construction Material LLC (CCM) shall have no other liability with respect thereto. Any claim regarding a product defect must be received in writing within one year of the date of shipment. No claim will be considered without such written notice or after the specified time interval. The User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the Cornerstone Construction Material LLC (CCM) technical manager.

Revised: 3-18-2024 SR



[www.fastracproducts.com](http://www.fastracproducts.com)

816-380-4747

[sales@fastracproducts.com](mailto:sales@fastracproducts.com)

Lee's Summit, MO 64081