



ROAD Rx

SOIL STABILIZER AND DUST SUPPRESSANT



Technical Data Sheet

PRODUCT DESCRIPTION

FasTrac ROAD Rx is a unique hybrid chemistry soil stabilization and dust suppressing agent. FasTrac ROAD Rx is an environmentally safe, easy to use concentrate that is diluted with water to bond and stabilize soil and gravel road substrates. FasTrac ROAD Rx may also be used as a sub base stabilizer at depths up to 12 inches.

APPLICATIONS

- Unpaved Roads
- Trails and Cart Paths
- Quarry Roads
- Construction Sites

FEATURES

- Environmentally Safe
- Hybrid Concentrate
- Easy To Use
- Binder and Dust Suppressant

MIXING / DILUTION RATES

Dilute FasTrac ROAD Rx 100:1 with water. Mix until concentrate is uniformly dispersed in water.

TYPICAL APPLICATION RATES

- 1 gallon of FasTrac ROAD Rx - 9 to 10 square feet at 2 inch (50 mm) depth stabilization.
- 2 gallons of FasTrac ROAD Rx - 18 to 20 square feet at 2 inch (50 mm) depth stabilization.
- 2 gallons of FasTrac ROAD Rx - 9 to 10 square feet at 4 inch (100 mm) depth stabilization.
- 3 gallons FasTrac ROAD Rx - 9 to 10 square feet at 6 inch (150 mm) depth stabilization.
- For deeper applications, contact Cornerstone Construction Materials.

PREPARATION

For best results, temperatures should be 50 F (10 C) and rising. For soil stabilization uses, scarify, till or loosen dirt or gravel surface at a depth of 4 to 10 inches (100 mm to 250 mm). For dust suppressant uses, scarify, till or loosen surfaces to a depth of 1 to 3 inches (25 mm to 75 mm). Wet surfaces with water followed by FasTrac ROAD Rx based upon recommended dilution and coverage rates.

CLEAN UP

Clean tools and equipment with water after final use.



 www.fastracproducts.com

 816-380-4747

 sales@fastracproducts.com

 Lee's Summit, MO 64081



ROAD Rx

SOIL STABILIZER AND DUST SUPPRESSANT

PACKAGING AND YIELD

55 Gallon Drums
275 Gallon Totes

SHELF LIFE AND STORAGE

2 years from date of manufacture when stored in dry weatherproof conditions. Storage Temperatures: 40° F (4.4°C) to 95° F (35° C). Do not allow to freeze.

TYPICAL PROPERTIES at 75° F (23.8° C)

TEST METHOD		RESULTS
ASTM D1633 Compressive Strength		
	1 Day	45 psi (0.31MPa)
	7 Days	55 psi (0.38 MPa)
Dry Unit Weight		85 pcf

HEALTH AND SAFETY INFORMATION

Product contains epoxy resin and amines. Wear proper PPE when using this product, including gloves, eye and skin protection and NIOSH / MSHA approved respirator or dust mask. Read SDS thoroughly before use. Prop 65: This product contains chemicals known by the state of California to cause cancer.

LIMITED WARRANTY

LIMITED WARRANTY All information provided by Cornerstone Construction Material LLC (CCM) concerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled, and applied under normal conditions in accordance with CCM's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of CCM's control are such that CCM assumes no liability for the provision of such information, advice, recommendations, or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations, or instructions related to its products. The user of the CCM product(s) must test the product(s) for suitability for the intended application and purpose before proceeding the full application of the product(s). CCM reserves the right to change the properties of its products without notice. All sales of CCM product(s) are subject to its current terms and conditions of sale. Prior to each use of any CCM product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Safety Data Sheet which are available at www.ccmaterial.com. Nothing contained in any CCM materials relieves the user of the obligation to read and follow the warnings and instructions for each CCM product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. CCM warrants this product for one year from the date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet when used in accordance with the written instructions. User determines suitability of product for intended use and assumes all risks. The buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CCM SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. CCM SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Every reasonable effort is made to apply exacting standards both in the manufacture of "FastTrac Road Rx" product and in the information which we issue concerning these products and their use. We warrant our products to be good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only on quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, Cornerstone Construction Material LLC (CCM) makes no warranty or guarantee, express or implied, including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Construction Material LLC (CCM) shall have no other liability with respect thereto. Any claim regarding a product defect must be received in writing within one year of the date of shipment. No claim will be considered without such written notice or after the specified time interval. The User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the Cornerstone Construction Material LLC (CCM) technical manager.

4-30-2025_SR

CEMENTS | CONCRETES | EPOXIES | GROUTS | MORTARS | MIXING SYSTEMS | OVERLAYS

Western Material Design · 1150 SE Hamblen Road, Lee's Summit, MO 64081