



Technical Data Sheet

PRODUCT DESCRIPTION

FasTrac CE335 Epoxy Penetrating Sealer is a two component, 100% solids, moisture tolerant, very low viscosity penetrating sealer for bridge decks, pavement, and slabs. Effective on dry or damp substrates, FasTrac CE335 Epoxy Penetrating Sealer penetrates deep into substrates to protect concrete structures from freeze thaw and chloride ion penetration.

APPLICATIONS

- Bridge Decks
- Airport Runways
- Parking Decks
- Pavement

FEATURES

- Very Low Viscosity
- 100% Solids
- Dry or Damp Surfaces
- 1:1 Ratio

SURFACE PREPARATION

Minimum substrate temperature is 500F (100C). Condition material to between 65°F and 85°F (18.3°C and 29.4°C). Substrate and surfaces must be clean and sound – blow out cracks with oil free compressed air to remove dust and debris. For flood coat applications, shotblast or sandblast all contact surfaces to remove all loose, broken, or unsound material, as well as any bond-inhibiting contaminants. Blow out all contact surfaces with oil free compressed air. Concrete surfaces must be clean, dry, and free of standing water prior to product installation.

MIXING

Mix Components A and B at a 1:1 ratio by volume. Pour Components A and B in equal volume into suitable mixing container. Mix with slow speed drill and paddle or similar mixer for 2 to 3 minutes. Do not whip air into liquids during mixing. Use immediately after mixing.

INSTALLATION

Flood area with product and roll out with squeegee, roller, or broom. Avoid excessive ponding. Apply until rejection. Where required, broadcast fine sand or concrete dust immediately and before the material hardens. Remove excess by vacuum or compressed air once material has hardened.

CURING

Product is self-curing. Do not add solvents. Protect from freezing temperatures, rain and traffic until minimum strength requirements are achieved.

CLEAN UP

All surfaces, tools and equipment may be cleaned with FasTrac Finishing Aid or a solvent based cleaner prior to material setting.



FasTrac CE330 Bridge Sealer

VERY LOW VISCOSITY PENETRATING SEALER

PACKAGING AND YIELD

2-gallon (7.56 liter), 10-gallon (37.8 liter), 110-gallon (416 Liter) and 500-gallon (1890 liters) units available. Approximate coverage of 50 - 150 square feet per gallon depending upon porosity of concrete.

SHELF LIFE AND STORAGE

Shelf life: 2 years from date of manufacture when stored in dry weatherproof conditions.

Storage Temperatures: 40° F (4.4°C) to 95° F (35°C).

TYPICAL PROPERTIES at 75° F (23.8° C)

TEST METHOD	RESULTS
Viscosity	≤ 250 cP
Gel Time	20 Minutes @ 70°F
ASTM D638 Tensile Strength	2,500 psi (17.2 MPa)
ASTM D638 Tensile Elongation	≥ 75%
ASTM D695 Compressive Strength	3,000 psi (20.9 MPa)
ASTM D695 Compressive Modulus	90,000 PSI (620 MPa)
ASTM C884 Thermal Compatibility	Pass
ASTM C882 Bond Strength	
	14 Days
ASTM D 570 Absorption	0.2% (24 hours)
AASHTO T 277 Chloride Ion Permeability	0.0 Coulombs
Tack Free	2 to 5 hours

HEALTH AND SAFETY INFORMATION

Product contains epoxy resin and amines. Wear proper PPE when using this product, including gloves, eye and skin protection and NIOSH / MSHA approved respirator or dust mask. Read SDS thoroughly before use. Prop 65: This product contains chemicals known by the state of California to cause cancer.

LIMITED WARRANTY

LIMITED WARRANTY All information provided by Cornerstone Construction Material LLC (CCM) concerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled, and applied under normal conditions in accordance with CCM's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of CCM's control are such that CCM assumes no liability for the provision of such information, advice, recommendations, or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations, or instructions related to its products. The user of the CCM product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). CCM reserves the right to change the properties of its products without notice. All sales of CCM product(s) are subject to its current terms and conditions of sale. Prior to each use of any CCM product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Safety Data Sheet which are available at www.ccmaterial.com. Nothing contained in any CCM materials relieves the user of the obligation to read and follow the warnings and instructions for each CCM product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. CCM warrants this product for one year from the date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet when used in accordance with the written instructions. User determines suitability of product for intended use and assumes all risks. The buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CCM SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. CCM SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Every reasonable effort is made to apply exacting standards both in the manufacture of "FasTrac CE330" product and in the information which we issue concerning these products and their use. We warrant our products to be good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only on quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, Cornerstone Construction Material LLC (CCM) makes no warranty or guarantee, express or implied, including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Construction Material LLC (CCM) shall have no other liability with respect thereto. Any claim regarding a product defect must be received in writing within one year of the date of shipment. No claim will be considered without such written notice or after the specified time interval. The User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the Cornerstone Construction Material LLC (CCM) technical manager.