



FasTrac CS100 Water Repellent

100% ACTIVE SILANE BASED WATER REPELLENT



Technical Data Sheet

PRODUCT DESCRIPTION

FasTrac CS100 Water Repellent is a silane based, breathable, deep penetrating, water repellent for concrete. The protective surface formed by FasTrac CS100 Water Repellent is extremely durable and protects concrete from corrosion via chlorides and weathering effects such as freeze thaw. FasTrac CS100 allows for continued normal vapor transmission rates of concrete, thus ensuring long term protection of concrete structures.

APPLICATIONS

- Bridge Decks
- Parking Structures
- Runways
- Precast Concrete

FEATURES

- Deep Penetrating
- Breathable
- Colorless
- Extremely Durable

SURFACE PREPARATION

Minimum substrate temperature is 20°F (-6°C) and rising. Best results are obtained when temperatures are between 50°F and 90°F (10°C and 35° C). Concrete should be structurally sound and have attained a minimum 75% of design strength. Clean all surfaces of paints, coatings and bond inhibiting substances. Sandblast or power wash surfaces as necessary to ensure clean and open surfaces for best penetration. Substrate should be dry or minimally damp before application.

MIXING & INSTALLATION

Stir material thoroughly prior to use. Apply uniformly using a low-pressure sprayer across all surfaces until concrete reaches saturation or rejection of sealer. Flat fan nozzles on spray wand work best to apply sealer. Squeegee or rollers may be used to further facilitate application after spray.

CURING

Dry time is typically 3 to 5 hours at 70°F (21°C) and longer in colder temperatures. Protect from rain and traffic until fully cured.

CLEAN UP

Collect any runoff or over-spray as necessary using absorbent material. Clean tools with xylene or similar solvent after use.



 www.fastracproducts.com

 816-380-4747

 sales@fastracproducts.com

 Lee's Summit, MO 64081



FasTrac CS100 Water Repellent

100% ACTIVE SILANE BASED WATER REPELLENT

PACKAGING AND YIELD

1-gallon (3.8 liter), 5-gallon (18.8 liter), 55-gallon (208 liter) and 250-gallon (946 liter) units.
Typical coverage: 100 to 200 square feet per gallon for normal concrete substrates.

SHELF LIFE AND STORAGE

18 months shelf life when stored in dry, weatherproof conditions. Storage temperatures are 40°F to 95°F (4.4°C to 35°C).

TYPICAL PROPERTIES at 75° F (23.8° C)	
TEST METHOD	RESULTS
Viscosity	≤ 20 cps
VOC's	≤ 350 g / L
Weight Per Gallon	7.3 lbs/gallon
Flash Point	≥ 149°F (65°C)
ASTM D5095 Active Content	100%
NCHRP-244 Series II Water Weight Gain Reduction	≥ 84% reduction
NCHRP-244 Series II Chloride Ion Reduction	≥ 86%
NCHRP-244 Series II Depth of Penetration	≥ 0.3 inch
Dry Time	2 to 4 hours

HEALTH AND SAFETY INFORMATION

Product contains epoxy resin and amines. Wear proper PPE when using this product, including gloves, eye and skin protection and NIOSH / MSHA approved respirator or dust mask. Read SDS thoroughly before use. Prop 65: This product contains chemicals known by the state of California to cause cancer.

LIMITED WARRANTY

LIMITED WARRANTY All information provided by Cornerstone Construction Material LLC (CCM) concerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled, and applied under normal conditions in accordance with CCM's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of CCM's control are such that CCM assumes no liability for the provision of such information, advice, recommendations, or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations, or instructions related to its products. The user of the CCM product(s) must test the product(s) for suitability for the intended application and purpose before proceeding the full application of the product(s). CCM reserves the right to change the properties of its products without notice. All sales of CCM product(s) are subject to its current terms and conditions of sale. Prior to each use of any CCM product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Safety Data Sheet which are available at www.ccmaterial.com. Nothing contained in any CCM materials relieves the user of the obligation to read and follow the warnings and instructions for each CCM product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. CCM warrants this product for one year from the date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet when used in accordance with the written instructions. User determines suitability of product for intended use and assumes all risks. The buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CCM SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. CCM SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Every reasonable effort is made to apply exacting standards both in the manufacture of "FasTrac CS100" product and in the information which we issue concerning these products and their use. We warrant our products to be good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only on quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, Cornerstone Construction Material LLC (CCM) makes no warranty or guarantee, express or implied, including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Construction Material LLC (CCM) shall have no other liability with respect thereto. Any claim regarding a product defect must be received in writing within one year of the date of shipment. No claim will be considered without such written notice or after the specified time interval. The User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the Cornerstone Construction Material LLC (CCM) technical manager.

4-6-2026_SR

CEMENTS | CONCRETES | EPOXIES | GROUTS | MORTARS | MIXING SYSTEMS | HFST

Cornerstone Construction Materials · 1150 SE Hamblen Road, Lee's Summit, MO 64081