



FasTrac CS309 WB

WATER-BASED CONCRETE CURE AND SEAL



Technical Data Sheet

PRODUCT DESCRIPTION

FasTrac CS309 WB is a water based, modified acrylic compound for sealing, curing and dustproofing freshly placed concrete. FasTrac CS309 WB effectively seals concrete substrates and provides added resistance to freeze thaw, chloride ion penetration and drying shrinkage. FasTrac CS309 WB is easily applied, VOC compliant and meets the requirements of ASTM C309, Type I, Class A/B and AASHTO M148, Type I, Class A/B.

APPLICATIONS

- Bridge Decks and Roads
- Parking Garages
- Warehouse Floors
- Columns and Beams

FEATURES

- Meets ASTM C309 Type I
- Improved Concrete Durability
- Dust Proofs Concrete
- VOC Compliant

USE

Condition material to 65°F – 85°F (18°C – 29°C) before using.

NEW CONCRETE: Apply FasTrac CS309 WB via low pressure sprayer after concrete bleed water has disappeared. Apply uniformly over all surfaces. Avoid puddling. A visible wet sheen should be observed after application. Do not puddle.

OLD CONCRETE: Surfaces must be clean and sound. Remove all curing compounds, paints, markings and loose concrete. Pressure washing of surfaces is recommended. Apply via low pressure sprayer uniformly across all surfaces until a uniform sheen is observed. Do not puddle.

COVERAGE

200 to 400 ft² per gallon

PACKAGING AND YIELD

- 1 gallon (3.78 L)
- 5 gallon (18.9 L)
- 55 gallon (208 L)

SHELF LIFE AND STORAGE

18 months in original unopened container. Storage temperatures 40°F to 95°F (4.4°C to 35°C).

TYPICAL PROPERTIES at 73° F (23° C)	
TEST METHOD	RESULTS
Flash Point	>200°F (93°C)
Freezing Point	32°F (0°C)
Flammability	None
VOC	< 100 g/L
Drive Time / Recoat Time	2-3 hours
Light Foot Traffic	2-3 hours
Normal Traffic	12 hours

HEALTH AND SAFETY INFORMATION

Use proper PPE when using this product, including eye protection, gloves and skin protection. Contains ethers. Read SDS thoroughly before use. Proposition 65 - This product contains material listed by the state of California as known to cause birth defects or other reproductive harm.

LIMITED WARRANTY

LIMITED WARRANTY All information provided by Cornerstone Construction Material LLC (CCM) concerning CCM products, including but not limited to, any recommendations and advice relating to the application and use of CCM products, is given in good faith based on CCM's current experience and knowledge of its products when properly stored, handled, and applied under normal conditions in accordance with CCM's instructions. In practice, the differences in materials, substrates, storage and handling conditions, actual site conditions and other factors outside of CCM's control are such that CCM assumes no liability for the provision of such information, advice, recommendations, or instructions related to its products, nor shall any legal relationship be created by or arise from the provision of such information, advice, recommendations, or instructions related to its products. The user of the CCM product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with the full application of the product(s). CCM reserves the right to change the properties of its products without notice. All sales of CCM product(s) are subject to its current terms and conditions of sale. Prior to each use of any CCM product, the user must always read and follow the warnings and instructions on the product's most current Technical Data Sheet, product label and Safety Data Sheet which are available at www.ccmaterial.com. Nothing contained in any CCM materials relieves the user of the obligation to read and follow the warnings and instructions for each CCM product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use. CCM warrants this product for one year from the date of installation to be free from manufacturing defects and to meet the technical properties on the current Technical Data Sheet when used in accordance with the written instructions. User determines suitability of product for intended use and assumes all risks. The buyer's sole remedy shall be limited to the purchase price or replacement of product exclusive of labor or cost of labor. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. CCM SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. CCM SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

Every reasonable effort is made to apply exacting standards both in the manufacture of "FasTrac CS309 WB" product and in the information which we issue concerning these products and their use. We warrant our products to be good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only on quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, Cornerstone Construction Material LLC (CCM) makes no warranty or guarantee, express or implied, including warranties of fitness for a particular purpose or merchantability, respecting its products, and Cornerstone Construction Material LLC (CCM) shall have no other liability with respect thereto. Any claim regarding a product defect must be received in writing within one year of the date of shipment. No claim will be considered without such written notice or after the specified time interval. The User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the Cornerstone Construction Material LLC (CCM) technical manager.

04-30-2026_SR



www.fastracproducts.com



816-380-4747



sales@fastracproducts.com



Lee's Summit, MO 64081